



310.217.2378 STEPSTONEDEALER.COM







SHORT FORM SPECIFICATION

SIZES:

......

CLASSIC

14" X 24" X 2 ½"

INSIDE AND OUTSIDE CORNERS
INSIDE RADIUS: 1, 2, 3, 4, 6, 8'
OUTSIDE RADIUS: 2, 3, 4, 6, 8'
1" RADIUS BULLNOSE WITH ¼" TOP
AND BOTTOM REVEAL

MODERN 18" X 18" X 2" 18" X 24" X 2" STRAIGHTS AND OUTSIDE CORNERS 1" RADIUS BULLNOSE

....

ALL SIZES ARE NOMINAL

RISER BLOCK 3" X 4" X 24" RISER TILE 6" X 12" X 1" 12"X 24"X 2 ½" 16"X 24"X 2 ½" 16"X 36"X 2 ½" 16"X 16"X 2 ½" 16"OUTSIDE CORNERS OUTSIDE RADIUS: 2', 4', 6', 8'

SQUARE MODULAR

MATERIAL: 4,000 PSI HARDROCK CONCRETE, TYPE III CEMENT

FINISH: SMOOTH, VERANOSTONE® OR HERMOSASTONE®

COLOR CHOICE: USING ACTUAL SAMPLES IS STRONGLY RECOMMENDED

DETAILS: VISIT STEPSTONEDEALER.COM FOR DRAWINGS AND DIMENSIONS

GRANADA WHITE	FRENCH GRAY	ICEBERG GREEN	ALMOND	CAFE BROWN	CARAMEL
501	504	505	506	507	510
AGAVE	PORCELAIN	BRICK RED	KONA	PEBBLE	ADOBE
512	513	516	521	524	525
GRANADA WHITE	FRENCH GRAY	ICEBERG GREEN	ALMOND	CAFE BROWN	CARAMEL
2001	2004	2005	2006	2007	2010
AGAVE	PORCELAIN	BRICK RED	KONA	PEBBLE	ADOBE
2012	2013	2016	2021	2024	2025

PLEASE NOTE: ALL OF OUR PRODUCTS ARE MADE BY HAND FROM NATURAL MATERIALS. VARIATIONS IN COLOR ARE TO BE EXPECTED. TO CONFIRM COLOR, PLEASE REFER TO ACTUAL CONCRETE SAMPLES BEFORE PLACING ORDER. SOME MINOR CHIPPING MAY RESULT FROM SHIPPING, BUT IS NOT DETRIMENTAL TO APPEARANCE OR FUNCTION. STEPSTONE, LLC RECOMMENDS SEALING TO AID IN GROUT REMOVAL AND CLEANING PRIOR TO INSTALLATION. GROUT NATURALLY WILL BOND WITH CONCRETE. IMMEDIATELY REMOVE ANY GROUT SLURRY THAT COMES IN CONTACT WITH THE FINISHED FACE OF THE PRECAST CONCRETE PIECES. ALL SIZES ARE NOMINAL. SEE DETAILS FOR FURTHER INFORMATION. AVAILABLE IN OTHER STANDARD COLORS. SEE ACTUAL COLOR CONCRETE SAMPLES BEFORE ORDERING. THIS MATERIAL IS COPYRIGHTED AND IS INTENDED SOLELY FOR THE USE OF CUSTOMERS OF STEPSTONE, LLC

06-2024