17025 SO. MAIN ST. GARDENA, CA 90248 310.217.2378
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 stepstonedealer.com

#### **MATERIAL PRODUCT DATA SHEET**

#### **Product Name**

**Truncated Dome Paver** 

# Manufacturer

 Stepstone, LLC
 Phone
 310-217-2378

 17025 So. Main St.
 Fax
 310-694-9060

 Gardena, CA 90248
 Toll free
 800-572-9029

### **Product Description**

Stepstone, Inc. has produced high quality pre-cast concrete since 1963. Truncated Dome Pavers are precast, A.D.A. compliant, detectable warning surface pavers that are designed to be used in commercial as well as public works applications. Pavers have an aligned dome pattern.

# **Composition & Materials**

Truncated Dome Pavers are hand-made, wet-cast from 4000 PSI hard rock concrete using Type III cement.

#### Sizes

Truncated Dome Pavers are available in the standard sizes 11-7/8" x11-7/8" x 2" and 23-7/8" x 23-7/8" x 2".

### **Finishes**

Truncated Dome Pavers available finishes include: Domed stippled finish or Veranostone® sandblast

# **Colors**

Truncated Dome Pavers are available in 15 standard colors: Custom Federal Yellow FS 33538, Yellow, Charcoal, Adobe, Agave, Almond, Brick Red, Café Brown, Caramel, French Gray, Granada White, Iceberg Green, Kona, Pebble, and Porcelain. Custom colors are available upon request; minimum order required.

# **Technical Data**

APPLICABLE STANDARDS: American Society for Testing & Materials (ASTM)

ASTM C33 - Standard Specification for Concrete Aggregates

ASTM C39 - Concrete Compressive Strength

ASTM C150 - Standard Specification for Portland Cement

ASTM C642 - Water Absorption, Density, Voids in Hardened Concrete

ASTM C666 - Rapid Freeze/Thaw Resistance of Concrete

ASTM C979 - Pigments for Integrally Colored Concrete

ASTM E303 - Pendulum Slip Resistance

### **Physical/Chemical Properties**

Truncated Dome Paver weight is 22 LBS per square foot. Water absorption: Not more than 6.0 % average, not more than 7.0 % for any individual unit for standard colors. Unit length, width and height are not more than +/-1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.